acer

Enlighten Your Bright Ideas Everywhere !

Acer **XD1270D**

DLP™
A TEXAS INSTRUMENTS TECHNOLOG

Downloaded from www.Manualslib.com manuals search engine

Specifications	Acer XD1270D
Projection System	DLP™
Resolution	Native XGA (1,024 x 768), Maximum SXGA (1,280 x 1,024)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards SXGA, SVGA, VGA (resizing)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2200:1
Displayable Colors	16.7 Million Colors
Brightness	2,300 ANSI Lumens (Standard), 1,840 ANSI Lumens (ECO)
Projection Lens	F / 2.35 ~ 2.47, f = 21.83mm ~ 23.81mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size (Diagonal)	23.1" (0.59m) ~ 302" (7.68m)
Projection Distance	3.28' (1m) ~ 39.4' (12m)
Throw Ratio	50.4"@2m
Horizontal Scan Rate	31.5 ~ 100 kHz
Vertical Refresh Scan Rate	56 ~ 85 Hz
Lamp Type	200 W User Replaceable UHP Lamp
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Keystone Correction	+/-16 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	Yes
Audio	One Internal Speaker with 2 watts Output
Weight	4.8 lbs (2.17Kg)
Dimension	230 x 238 x 123 mm (9.1" x 9.4" x 4.8")
IR Remote Control	Laser Pointer & Mouse function & PgUp/PgDn function
Digital Zoom	Yes
Picture in Picture	N/A
Wireless	N/A
Power Supply	AC Input 100~240V auto-switching power supply
Power Consumption	253 Watts (Operation), 14 Watts (Standby)
Operation Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	32 dBA (Standard mode), 28 dBA (ECO mode)
Uniformity	90%

Other Features

1. **Empower Key**
   A quick button on remote control or projector control panel for user easily to perform the following three Acer unique features.
2. **Acer eView Management**
   A feature which allows user easily to select the optimal display mode for specific display content.
3. **Acer eTimer Management**
   A feature which allows user to enable a Timer function during the presentation. A digit clock will be displayed on the screen while the timer is in counting. A reminder on the screen and an alarm sound will be activated when time is up.
4. **Acer eOpening Management**
   A feature which allows user to customized their desired projector startup screen.
5. **Auto Shutdown**
   A feature which allows the projector automatically turned off according to the setting time via OSD if the projector continuously no signal input
6. **Alarm sound**
   A feature which enables the projector to play the alarm sound under various conditions described below:
   a) Projector turn on b) Projector turn off
   c) Time is up for the eTimer function d) Projector function error
7. **Quick Start**
   The projector starts projecting within 15 seconds after power button being pressed
8. **Quick Shutdown**
   The projector shuts down within 30 seconds after power button being pressed
9. **Security**
   A feature which enables the password control capability of the projector. It prevents the projector from unauthorized usage. Also, it reduces the possibility of the projector's being stolen
10. **Quick Detection**
    The projector can immediately detect signal as soon as any source input to the projector. No need to waste your time to wait for the signal scanning.
11. **Advanced 5-Segment Color Wheel**
    Utilize 5-segment color wheel with additional yellow segment offering great color correctness
12. **Dual VGA input supported**
    Except for original D-Sub connector, the DVI-I connector can also supports analog VGA signal. With the dual VGA input support, the projector offers better flexibility of connectivity

I/O Connectors

Computer Input:
- 1 HDB 15-Pin D-Sub (VGA/Component/HDTV)
- 1 3.5mm Audio Mini Jack
- 1 RS232 Connector
- 1 29-pin DVI-I Connector (VGA/Component/HDTV/HDCP)

AV Input:
- 1 HDB 15-Pin D-Sub (VGA/Component/HDTV, same as above)
- 1 Composite Video RCA Jack
- 1 S-Video Mini DIN
- 1 3.5mm Audio Mini Jack (Same as above)
- 1 29-pin DVI-I Connector (the same one as the above)

Output:
- 1 15-Pin D-Sub for Monitor Loop Through
- 1 USB Connector for Remote Computer Control

Standard Accessories

AC Power Cord
VGA Cable (15pin D-Sub)
Composite Video Cable (RCA)
DVI Cable
S-Video Cable
VGA (D-Sub) to Component / HDTV Adapter
USB Cable
Audio Cable (Mini to Mini Phone Jack)
Remote Control with Laser Pointer & Mouse & PgUp/PgDn function
Batteries x 2 for Remote Controller
User's Guide (CD-ROM)
Quick Start Card
Lens Cap
Carrying Case

2 Years Warranty Projector (ค่าแรง/อะไหล่)

หลอดภาพรับประกัน 1 ปี
หรือ 1,000 ชั่วโมง

บริษัท เอเซอร์ คอมพิวเตอร์ จำกัด

Acer Call Center 0-2685-4311
www.acer.co.th

191/62-63 ชั้น 16 อาคารซีทีไอ ทาวเวอร์ ถ.รัชดาภิเษกคลองเตย กรุงเทพฯ 10110
โทรศัพท์ 0-2661-9700 โทรสาร 0-2661-9721
http://www.acer.co.th

Downloaded from www.Manualslib.com manuals search engine